


SMART POWER SENSOR

Model: SmartPS-250A-T0

DTSU666-H 250A/50mA




YDS60-C24



DTSU71



DHSU1079-CT



Accurate
Class I Measurement
Accuracy



Simple & Easy
LCD Display, Easy to Set
and Check



Energy Efficient Overall
Power Consumption $\leq$
1.5 W

SmartPS-250A-T0 Technical Specifications

Technical Specification	SmartPS-250A-T0			
	DTSU666-H 250A/50mA	YDS60-C24	DTSU71	DHSU1079-CT
General Specification				
Dimensions (H x W x D)	100mm x 72mm x 65.5mm	101mm x 72mm x 66mm	100mm × 72mm × 66mm	99mm × 72mm × 66mm
Mounting type	DIN35 Rail			
Weight (including cables)	0.3kg	0.285kg	0.248kg	0.26kg
Power Supply				
Power grid type	3P3W/3P4W			
Input voltage (phase voltage)	230 V AC/400 V AC			
Power consumption	<1.5W			
Measurement Range				
Line voltage	304V–500V			
Phase voltage	176 V AC–288 V AC			
Current	0–250A			
Measurement Accuracy				
Current/Voltage	±0.5%			
Power/Energy	±1%			
Frequency	±0.01 Hz			
Communication				
Interface	RS485			
Baud rate	4800/9600(Default)/19200/115200			
Communication protocol	Modbus-RTU			
Environment				
Operating temperature range	–25°C to +60°C	–25°C to +60°C	–25°C to +60°C	–25°C to +60°C
Storage temperature range	–40°C to +85°C	–40°C to +85°C	–35°C to +70°C	–40°C to +85°C
Operating humidity	5% RH–95% RH (non-condensing)			
Others				
Accessories	RS485 Cable (10 m / 33 ft.)			
	3 CT 250 A/50 mA			